



"Innovative Solutions for A Better Life"

## UF U-210 : Hollow Fiber Ultrafiltration Cartridge



<b>DIMENSION</b>	<b>Nominal Diameter</b>	2,5 inch
	<b>Length</b>	24,7 cm
	<b>Feed/Concentrate Connection</b>	-
	<b>Permeate Connection</b>	-
	<b>Weight</b>	470 gram
<b>FEATURES</b>	<b>Permeate Capacity</b>	50 liter/hour
	<b>Permeate Turbidity</b>	<3 NTU
	<b>Filtration Mode</b>	Shell to Lumen (Dead End)
	<b>Membrane Material</b>	Polypropylene
	<b>Pore size</b>	0,01 micron
	<b>Potting Material</b>	Epoxy Resin
	<b>Housing Material</b>	PVC
	<b>Storage Solution</b>	0,1% Sodium Metabisulfite
<b>OPERATION</b>	<b>Operating pressure</b>	0,5 - 1,5 bar
	<b>Operating temperature</b>	max. 50 °C

*The information contained in this publication is believed to be accurate and reliable, but is not to be construed as implying any warranty or guarantee of performance. We assume no responsibility, obligation or liability for results obtained or damages incurred through the application of the information contained herein.*

---

**GDP Filter - Filtration and Separation System**

**Jl. Cihanjuang No. 124 Km. 2,5 - Bandung 40559, Indonesia**

**Ph. : (022) 6648498, Fax. : (022) 6652139, E-mail : support@gdpfilter.co.id; Web : www.gdpfilter.co.id**